

# Material Specification

## GreenWeave



KE FIBERTEC

AIR THE WAY YOU WANT

**MATERIAL:** High Dust Capacity polyester material woven by KE Fibertec Væveri (textile mill). The GreenWeave materials are woven in a twill weave that combined with the heavy and twisted staple fibres ensures the largest possible textile surface and by that longer washing intervals.

**CONSTRUCTION:** Heatset, shrinkage- and permeability-stabilised material.

Type KE-Datasheet		GW50 1	GW150 2	GW200 3	GW320 4	GW500 5	GW780 6	GW1380 7	Standard
<b>Weight (%) -/+5</b>	<b>g/m<sup>2</sup></b>	400	330	325	300	290	325	340	EN-ISO 5077
<b>Thickness (%) -/+10</b>	<b>mm</b>	0.7	0.6	0.6	0.6	0.65	0.7	0.6	EN-ISO 12127:1997
<b>Permeability</b>	<b>m<sup>3</sup>/m<sup>2</sup>/h 120 Pa Tolerance (%)</b>	50 -25/+8	150 -12/+16	200 -7/+19	320 -6/+15	500 -6/+15	780 -8/+14	1380 -11/+14	EN-ISO 9237:1995
<b>Tensile strength (%) -/+10</b>	<b>Warp / Weft N/50 mm</b>	2600 / 2100	2800 / 1100	2700 / 1300	2800 / 1100	2800 / 920	2900 / 1300	2700 / 1300	EN-ISO 13934-1
<b>Resistance to tearing (%) -/+10</b>	<b>Warp / Weft N</b>	98 / 103	112 / 69	95 / 72	167 / 91	178 / 137	225 / 227	144 / 138	EN-ISO 13937:2
<b>*Filter class</b>		M6	M6	M6	M6	M6	M6	M6	EN 779:2012
<b>*Dust holding capacity</b>	<b>(250/350/450 Pa) g</b>	11/19/28	11/19/28	11/19/28	11/19/28	11/19/28	11/19/28	11/19/28	EN 779:2012
<b>**Shrinkage in wash</b>	<b>(%) 40°C</b>	0.5	0.5	0.5	0.5	0.5	0.5	0.5	EN-ISO 5077
<b>Operating temperature</b>	<b>°C</b>	80/-45	80/-45	80/-45	80/-45	80/-45	80/-45	80/-45	
<b>Spontaneous ignition temp.</b>	<b>°C</b>	508	508	508	508	508	508	508	
<b>Water absorption</b>	<b>(%) at 90% RH</b>	0.4	0.4	0.4	0.4	0.4	0.4	0.4	
<b>Electrostatic resistance</b>	<b>Ohm</b>	≤2 x 10 <sup>10</sup>	≤2 x 10 <sup>10</sup>	≤2 x 10 <sup>10</sup>	≤2 x 10 <sup>10</sup>	≤2 x 10 <sup>10</sup>	≤2 x 10 <sup>10</sup>	≤2 x 10 <sup>10</sup>	DIN 54345-1
<b>Clean room classification</b>		N/A	N/A	N/A	N/A	N/A	N/A	N/A	ISO-14644-1
<b>Fire resistance</b>		B-S1-d0 Yes	B-S1-d0 Yes	B-S1-d0 Yes	B-S1-d0 Yes	B-S1-d0 Yes	B-S1-d0 Yes	B-S1-d0 Yes	EN-13501 UL 2518 NFPA 90 A
<b>Oeko-Tex®</b>		Approved	Approved	Approved	Approved	Approved	Approved	Approved	Standard 100
<b>Cradle to Cradle®</b>	The GreenWeave material is Cradle to Cradle certified								

\*KE measurement \*\*Washed and dried according to KE Fibertec instructions

This document and all information thereon is the property of KE Fibertec AS. It must not be copied, imparted to a third party or used for any other purpose without the written consent of KE Fibertec AS.

10/2021

KE Fibertec AS  
Industrivej Vest 21  
DK-6600 Vejen

T: +45 7536 4200  
info@ke-fibertec.dk  
www.ke-fibertec.com

